

PRODUCT SPECIFICATION

NAME:		PET - RAM WS 12/180/B				
TYPE:		White soft petrolatum				
ISSUE DATE:		22/05/2007				
VALID FROM:		28/05/2007				
CANCEL AND SUBSTITUTE ISSUE OF:		24/11/2004				
ANALYSIS	MEASURE	METHOD	MIN.	MAX	TIP.	
Saybolt colour	---	ASTM D 156	+27			
Density at 100 °C	Kg/m ³	ASTM D 1298	810	830		
Congeaing point	°C	ASTM D 938	48	54		
Melting point	°C	ASTM D 127	55	60		
Cone penetration (25°C)	dmm	ASTM D 937	160	180		
Dynamic viscosity at 100 °C	cP	ASTM D 445	8.5	11		
UV absorption (270-279 nm)	Abs.	DAB 1997		0.32		
UV absorption (280-289 nm)	Abs.	DAB 1997		0.27		
UV absorption (290-299 nm)	Abs.	DAB 1997		0.24		
UV absorption (300-310 nm)	Abs.	DAB 1997		0.21		
UV absorption (350-400 nm)	Abs.	DAB 1997		0.05		
Appearance	---	ASTM D 4176/1	White, translucent, semisolid mass			
Readily carbonisable substance (70 °C)	--	DAB 1997	PASS			
Odour	---	-----	Nil			

MEETS SPECS: USP XXIII/NF; B.P. 98 ; DAB.



ISSUED (CTQ): 

APPROVED (Dds):

RA. M. OIL. S.p.A.
 RAFFINERIA MERIDIONALE OLI LUBRIFICANTI
 Via Filicchio, 16/A
 TAVERNANOVA di CASALNUOVO (NAPOLI)