

Aristoflex AVC

Polymeric sulfonic acid, partially neutralised

Global Product Specification

Country of Origin: Tarragona/Spain

<u>Item</u>	Specification	<u>Unit</u>	<u>Method</u>
Appearance	white powder		visual
Solid content	min. 92.0	%	Clariant
Water content Karl-Fischer	max. 7.0	%	DIN 51777
pH value 1% in deionised water, 20°C	4.0 - 6.0		DIN EN 1262
Viscosity Brookfield 1% in deionised water, 20°C	48000 - 65000	mPas	DIN EN ISO 2555

Remarks: Product is sieved - Mesh size 2mm

Product Code: 138240 Version: 1

Date of Issue: 11.01.2012

This product specification would cease to be binding if the customer has not purchased the product during the preceding 12 months. This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses . It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application . Any existing industrial rights must be observed. ISO-, EN- and DIN-Standards are published by: Beuth-Verlag, Burggrafenstr. 6, D-10787 Berlin, Germany. They are also available from the National Standard authority of each country. DGF-Standards are published by: Wissenschaftliche Verlagsgesellschaft mbH, Birkenwald Str. 44, D-70191 Stuttgart, Germany. This Product Specification is not signed. If you have any questions, please contact the local Clariant Office or Clariant Produkte (Deutschland) GmbH, European-Quality-Service-Center (EQSC), D-65926 Frankfurt, Germany. email: ICS.MS.QA.Rhein.Main@clariant.com *** Please visitour website http://www.clariant.com